



# Maxi-Heat®

## Dimensions

Height: 6' (1.83 m)

Length: 16' (4.88 m)

Width: 6' 8" (2.03 m)

Weight: 3,500 lbs. (1,587.6 kg) empty; 4,651 lbs. (2,109.7 kg) with fuel

## Engine (Standard)

Cat C1.5L diesel

Glow plug cold start aid, engine block heater, low oil pressure/high temperature auto shutoff

**Starting:** 12 volt electric-8D battery

## Heaters

Two I.C.E. Frost Fighter IDF 500 indirect fired heaters; up to 505,000 BTU/HR each

One 16" duct flange per heater

Optional flexible ducting easily connects to heater output flanges

Standard fuel pump pressure gauges

1.5" WC static pressure allows up to 110' of 16" ducting

**Heated Air Output:** Total of 5,700 cfm from two heaters

Temperature Rise: 185° F (85° C)

**Operating Time:** Up to 30 hours without refueling

## Generator

8 kw transformer regulated generator

## Standard Trailer Includes:

Trailer – formed, welded steel frame

Heavy-gauge steel enclosure

Lockable access doors

5,000 lb. (2268 KG) leaf spring axle with 15" (38.1 cm) wheels and tires

Safety chains

Adjustable height, reversible combination, 2" (50 mm) ball, 3" (75 mm) pintle hitch

Front screw jack

Hour meter

Interior compartment light

Turn signals, brake and taillights

## Fuel System

Fuel requirements: No. 1 fuel oil or blend

Fuel Consumption:

Engine: 0.5 gph (2.2 Lph)

Heater: Up to 3.5 gph (15.9 Lph) for 500,000 btu per heater (non-CSA Model)

Fuel Capacity: 191.1 gal. (723.4 L)